

## Pt1000TGL40/E - sonda temperatury Pt1000 z kablem o długości 2m

kod: SN186E



Niedroga, wielozadaniowa, wodoszczelna (IP67) sonda temperatury o zakresie pracy -30 to +80°C.

Gilza ze stali kwasoodpornej 1.7241, kabel w izolacji z PVC o określonej długości, ze złączem ELKA. Średnica gilzy 5.7mm, długość 40mm. Stała czasowa  $t_{63} < 10s$ ,  $t_{95} < 30s$ , mierzona w cieczy. Stała czasowa  $t_{63} < 60s$ ,  $t_{95} < 150s$ , mierzona w powietrzu 1m/s.

### Dane techniczne

TEMPERATURE SENSOR	
Measuring range	-30 to +80 °C
Accuracy	$\pm (0.15 + 0.002 t)$ at °C
Accuracy class	A
Time response	$t_{0.5} < 7 s$ (in flowing water at $> 0.2 m/s$ ) $t_{63} < 10s$ , $t_{95} < 30s$ (in liquid) $t_{63} < 60s$ , $t_{95} < 150s$ (air flow 1m/s)
Type of sensing element	Pt1000
Temperature coefficient	3850 ppm / °C
GENERAL TECHNICAL DATA	
Wire connection	2-wire connection
Material of the case	stainless steel DIN 1.4571
Dimensions of the case	length 40 mm; diameter $5.7 \pm 0.1 mm$
Lead-in cable	PVC shielded
Length of lead-in cable	2 meters
Connector	ELKA
IP protection	IP67
Warranty	30 months